



Gulf Harmony AW Plus Super Clean

Premium quality super clean anti-wear hydraulic oil

Product Description

Gulf Harmony AW Plus Super Clean series are premium quality anti-wear hydraulic oils specially developed to meet the requirements of the most demanding modern hydraulic systems in industrial and mobile service requiring super clean oils. These oils are formulated with severely hydroprocessed Group II base oils and a carefully selected additive system to satisfy the performance requirements of a wide range of hydraulic equipment. They possess outstanding thermo-oxidative stability, anti-wear property, rust & corrosion protection, water separation & air-release properties and hydrolytic stability to prolong the equipment and oil life. They exceed the performance requirements of global industry standards viz. DIN 51524 Part 2-HLP, AFNOR NFE 48-603 (HM) & ISO 11158 HM and majority of the international OEMs viz. Denison, Cincinnati Lamb & Eaton.

Features & Benefits

- Outstanding thermo-oxidative stability reduces deposit formation, improves pump & valve performance and allows extension of oil and filter change intervals
- Exceptional anti-wear property results in fewer breakdowns, longer pump life and reduced maintenance costs
- Superior cleanliness of this oil ensures smooth & trouble-free operation of precision control hydraulic systems employing close clearance servo valves
- Excellent demulsibility helps in faster separation of water from oil and resists formation of emulsions
- Special rust & corrosion inhibitors protect multi-metallurgy components against negative effects of moisture presence in the system
- Rapid air release property minimises chances of pump cavitation and thus prevents component damage, reduces vibration and maintains efficiency especially in modern hydraulic systems where sump sizes are becoming smaller
- Offers long term hydrolytic stability and yellow metal compatibility in presence of water
- Compatible with multi-metals & most sealing materials used in hydraulic systems

Applications

- Most demanding hydraulic systems subjected to high pressures and loads requiring super clean oils
- Applications requiring extended oil change intervals
- Hydraulic systems in industrial and mobile service employing gear, vane and piston pumps where anti-wear hydraulic oils are recommended
- Mobile hydraulic fluid power transmission systems and general machine lubrication

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com



Specifications, Approvals & Typical Properties

ISO Viscosity grades	10	15	22	32	46	68	100		
Meets the following Specifications									
DIN 51524 Part 2-HLP	X	X	X	X	X	X	X		
AFNOR NFE 48-603 (HM), ISO 11158 HM	X	X	X	X	X	X	X		
Denison HF-0, HF-1, HF-2				X	X	X			
Cincinnati Lamb (formerly Cincinnati Machine)				P-68	P-70	P-69			
Eaton (Vickers) M-2950-S, M-2952-S, I-286-S				X	X	X			
Bosch Rexroth 07 075 for vane, piston & gear pumps, Sauer Danfoss 520L0463				X	X	X			
Typical Properties									
Test Parameters	ASTM Method	Typical Values							
Viscosity @ 40 °C, cSt	D 445	10.2	15.3	22.2	31	46.3	68.1	98.7	
Viscosity Index	D 2270	109	109	108	105	104	100	99	
Flash Point, °C	D 92	142	168	192	206	218	226	238	
Pour Point, °C	D 97	-33	-27	-27	-24	-24	-24	-15	
Density @ 15°C, Kg/l	D 1298	0.837	0.843	0.848	0.852	0.855	0.858	0.861	
Rust Test	D 665A/B	Pass	Pass	Pass	Pass	Pass	Pass	Pass	
Emulsion Test 30 minutes max	@ 54 °C @ 82 °C	D 1401	Pass	Pass	Pass	Pass	Pass	Pass	-
			-	-	-	-	-	-	Pass
Foam Test, foam after 10 minutes of settling for all sequences	D 892	Nil	Nil	Nil	Nil	Nil	Nil	Nil	
Turbine Oil Stability Test, hrs	D 943	3000+		4500+	5000+			4000+	
FZG, fail load stage, minimum	DIN 51354 Part II	-	-	-	11	11	11	11	
Cleanliness level (at filling stage)	NAS 1638	6	6	6	6	6	6	6	

December 2009

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com